

	Tragfähigkeit/load-carrying	P*	Rges	Ri	Ra	R0	H0	OT	B	Re
	kg	bar	mm	mm	mm	mm	mm	mm	mm	mm
Z-KL 90-3,0/2,5	90	5,6	3000	1600	1400	506	2500	1900	2785	2983
Z-KL 80-3,5/2,5	80	5,1	3500	1850	1650	566	2500	1900	2785	3479
Z-KL 60-4/2,5	60	4,1	4000	2100	1900	627	2500	1900	2785	3974
Z-KL 50-4,5/2,5	50	3,6	4500	2350	2150	689	2500	1900	2785	4470

* Erforderlicher Versorgungsdruck bei Verwendung des pneumatischen ZASCHE Seilbalancers Z-BP-110
Necessary supply pressure for ZASCHE pneumatic balancer Z-BP-110

** Max. UK 4m bei pneumatischem Hubgerät
Max. UK 4m for pneumatic hoist

Für Dübel HVZ M 10x75 (8x) gilt Mindestdicke des Bodens 150 mm.

For anchors HVZ M 10x75 (8x) is necessary a min 150 mm floor-thickness.

Mindest-Betonfestigkeitsklasse:

Nach DIN EN 206-1:2001-07

und DIN 1045-2:2001-07 : min. C 20/25 max. C 50/60

Nach DIN 1045:1988-07 : min. B 25 max. B 55

Strength of concrete:

After DIN EN 206-1:2001-07

and DIN 1045-2:2001-07 : min. C 20/25 max. C 50/60

After DIN 1045:1988-07 : min. B 25 max. B 55

Anwendungsbereich: Datenblatt Verbundanker beachten!

Range of application: See datasheet of chemical anchor!

Z-KL stehend / floor mounted

