

	Tragfähig- keit/SWL ⁽¹⁾	Hebe- zeug	Hubge- schwindig- keit	Rges	Ri	Ra	R0	H0**	OT	B	Re
	Kg		m/min	mm	mm	mm	mm	mm	mm	mm	mm
Z-KME 160-3/2,5	160	Z-RE-250	10	3000	1600	1400	535	2500	1900	2900	2986
Z-KME 140-3,5/2,5	140	Z-RE-250	10	3500	1850	1650	596	2500	1900	2900	3482
Z-KME 125-4/2,5	125	Z-RE-250	10	4000	2100	1900	657	2500	1900	2900	3978
Z-KME 100-3/2,5	100	Z-RE-100	24,8	3000	1600	1400	535	2500	1900	2900	2986
Z-KME 100-3,5/2,5	100	Z-RE-100	24,8	3500	1850	1650	596	2500	1900	2900	3482
Z-KME 100-4/2,5	100	Z-RE-100	24,8	4000	2100	1900	657	2500	1900	2900	3978

Tragfähigkeiten 100 kg und darunter können mit dem günstigeren Hebezeug Z-RE-100 umgesetzt werden.
SWL ⁽¹⁾ of 100 kg and below can be handled using the more affordable Z-RE-100 hoist.

* Erforderliche Stromversorgung 230V/50Hz 16A

Necessary power supply 230V/50Hz 16A

** Max. UK 3,5m bei elektrischem Hubgerät

Max. UK 3,5m for electric hoist

⁽¹⁾ SWL = safe working load

Für Dübel HVZ M 12x 95 (8x) gilt Minstdicke des Bodens 190 mm.

For anchors HVZ M 12 x 95 (8x) is necessary a min 190 mm floor-thickness.

Mindest-Betonfestigkeitsklasse:

Nach DIN EN 206-1:2001-07

und DIN 1045-2:2001-07 : min. C 20/25 max. C 50/60

Nach DIN 1045:1988-07 : min. B 25 max. B 55

Strength of concrete:

After DIN EN 206-1:2001-07

and DIN 1045-2:2001-07 : min. C 20/25 max. C 50/60

After DIN 1045:1988-07 : min. B 25 max. B 55

Anwendungsbereich: Datenblatt Verbundanker beachten!

Range of application: See datasheet of chemical anchor!

Z-KME stehend / floor mounted

